


UL Listed Photoluminescent Exit Sign





Features

Utilizes Advanced Photoluminescent Technology ®

- · No maintenance required no batteries or bulbs to replace
- Zero energy consumption
- · Safe, environmentally friendly, non-toxic, non-radioactive
- · Designed for surface, flag and ceiling mount
- Thin, low profile construction
- · Can be used for both high level and low level applications
- Tested and approved for low location
- · Zero energy consumption

Technical Information

Size: 8.5" x 15.75"

Background: Green, red, brushed aluminum/stainless steel,

or photoluminescent

Lettering: Photoluminescent, green or red lettering.

Visibility: 50 feet

Directional: Chevron kit included (Field Applied)

Frame construction: Brushed aluminum body/stainless steel.

Life Expectancy

25+ years

Power Requirements

No electrical source required.

Installation

Surface, flag or ceiling mounted options. Frame and Bracket are additional items. Before installation it must be determined that there is a minimum of 5 Fc of fluorescent light on the face(s) of the sign at all times during building occupancy.

Applications

Both high level and low level Suitable for floor proximity installation

Approvals:

Meets NFPA Life Safety Code 101 and OSHA Meets International Building and Fire Codes Listed through UL 924 for the USA and Canada

Ceiling Mount

