# **MAGIC SWITCH: MS08**


ADJUSTABLE RANGE TOUCHLESS ACTUATOR







#### PRIMARY APPLICATIONS



# DESCRIPTION

BEA's MS08 utilizes proven microwave motion technology to ensure consistent, dependable touchless activation and can be adjusted to comply with the ANSI 156.10 knowing act standard.

The MS08 detects moving objects such as a hand, cart or wheelchair and is ideal for use in hospitals, pharmacies, clean rooms, food service facilities and other applications requiring a hygienic activation method.

# FEATURES & BENEFITS


- Detection zone from 4 to 24 inches (pulse or toggle)
- Silent activation for hospitals and other • noise-sensitive environments
- Water-resistant foam gasket provides increased • reliability when exposed to liquid or cleaning products
- Low profile, beveled design reduces chance of • accidental damage in high traffic areas
- Available in white, black or cream faceplate; options for single or double gang boxes
- Multiple faceplate graphic options available •
- Inter-operates with all automatic door control • makes and models



BEA, Inc. **RIDC Park West** 100 Enterprise Drive Pittsburgh, PA 15275-1213 www.BEAinc.com

Customer Service: 800.523.2462 Technical Support: 800.407.4545


#### APPLICATIONS




#### TECHNICAL SPECIFICATIONS

Technology	Microwave Doppler Radar
Radiated Frequency Radiated Power Density	24.125 GHz 5 mW/cm <sup>2</sup>
Detection Mode	Motion (bidirectional)
Detection Range	4 to 24 inches (adjustable)
Output	Relay with switch-over contact (voltage free)
Max. Voltage Max. Current Max. Switching Power	60 VDC / 125 VAC 1 A (resistive) 30 W (DC) / 60 VA (AC)
Output Hold Time	0.5 s (in pulsed mode)
Supply Frequency	50 to 60 Hz
Supply Voltage	12 to 24 VAC ±10% 12 to 24 VDC +30% / -10%
Power Consumption	< 1.5 W
Material	ASA, Nylon, PC
Cable Type	Standard cable up to 16 AWG - 1.5 mm <sup>2</sup>
Temperature Range	-4°F to +131°F (-20°C to +55°C)
Norm Conformance	EMC: 2004 / 108 / EC; FCC: G9B-MS08; IC: 4680A-MS08

### DIMENSIONAL DRAWINGS





#### **RELATED PRODUCTS**





70.5272

SINGLE GANG

SOLID BLACK

70.5279

DOUBLE GANG

**BLACK WITH LOGO** 

70.5274

SINGLE GANG

SOLID WHITE

NAVE TO OPEN Ma,

70.5271

DOUBLE GANG

CREAM WITH TEXT



70.5273

DOUBLE GANG

SOLID BLACK

Mg)

70.5268

SINGLE GANG

WHITE WITH TEXT

70.5275

DOUBLE GANG

SOLID WHITE

70.5276

SINGLE GANG

SOLID CREAM



70.5227 DOUBLE GANG **BLACK WITH TEXT** 



70.5278 SINGLE GANG BLACK WITH LOGO



70.5269 DOUBLE GANG WHITE WITH TEXT



70.5270 SINGLE GANG CREAM WITH TEXT



70.5277 DOUBLE GANG SOLID CREAM



900 MHZ RETROFIT TRANSMITTER

CUSTOM PACKAGE

10RD900

900 MHZ RECEIVER

MODULE

MS08U CUSTOM - 10MS08U plus choice of any one of the additional faceplates

www.BEAinc.com © 2017 BEA, Inc. All rights reserved.

# MAGIC SWITCH: MS08 Adjustable range touchless actuator

>0.25 in

BEA, Inc. **RIDC Park West** 100 Enterprise Drive

Customer Service: 800.523.2462 Pittsburgh, PA 15275-1213 Technical Support: 800.407.4545



