# SAFETY DATA SHEET

# SECTION 1) CHEMICAL PRODUCT AND MANUFACTURER'S IDENTIFICATION

Product ID: 497720
Product Name: ZenaLube FG

Revision Date: Oct 2, 2019 Supersedes Date: Nov 18, 2016

Version: 1.1

Manufacturer's Name: Zenex International

Address: 1 Zenex Circle Cleveland, OH, US, 44146

**Emergency Phone:** 1-800-535-5053 **Information Phone Number:** (440)-232-4155

Fax:

Product/Recommended Uses: Food Grade Lubricant

# **SECTION 2) HAZARDS IDENTIFICATION**

#### Classification

Aerosols Category 1

Gases Under Pressure Liquefied Gas

# **Pictograms**





### Signal Word

Danger

# **Hazardous Statements - Physical**

H222 - Extremely flammable aerosol

H280 - Contains gas under pressure; may explode if heated

# **Precautionary Statements - General**

P101 - If medical advice is needed, have product container or label at hand.

P102 - Keep out of reach of children.

P103 - Read label before use.

### **Precautionary Statements - Prevention**

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 - Do not spray on an open flame or other ignition source.

P251 - Do not pierce or burn, even after use.

### **Precautionary Statements - Response**

No precautionary statement available.

### **Precautionary Statements - Storage**

P412 - Do not expose to temperatures exceeding 50°C / 122°F.

#### **Precautionary Statements - Disposal**

No precautionary statement available.

# **SECTION 3) COMPOSITION, INFORMATION ON INGREDIENTS**

CAS	Chemical Name	% By Weight
0008042-47-5	MINERAL OIL, SLAB OIL	51% - 90%
0000074-98-6	PROPANE	5% - 11%
0067784-80-9	Soybean oil, Me ester	5% - 10%
0000106-97-8	BUTANE	2% - 4%

Specific chemical identity and/or exact percentage (concentration) of the composition has been withheld to protect confidentiality.

### **SECTION 4) FIRST-AID MEASURES**

#### Inhalation

Remove to fresh air. Administer oxygen if needed. Apply artificial respiration if breathing has stopped. Get medical attention.

#### **Eye Contact**

Wash immediately with large volumes of fresh water for at least 15 minutes. Get medical attention.

#### **Skin Contact**

Wipe off with a towel. Wash with soap and water. Get medical attention if irritation persists.

### Ingestion

Ingestion is not a likely route of exposure. Get medical attention if you feel unwell.

# **SECTION 5) FIRE-FIGHTING MEASURES**

# Suitable Extinguishing Media

Foam, Alcohol foam, CO2, Dry Chemical, Water fog.

#### **Unsuitable Extinguishing Media**

Water may be ineffective but can be used to cool containers exposed to heat or flame.

#### Specific Hazards in Case of Fire

Closed containers may explode from internal pressure build-up when exposed to extreme heat and discharge contents. Liquid content of container will support combustion. Overexposure to decomposition products may cause a health hazard. Symptoms may not be readily apparent. Obtain medical attention. Hazardous decomposition products include carbon dioxide, carbon monoxide, and other toxic fumes.

# **Fire-Fighting Procedures**

Water may be used to cool containers to prevent pressure build-up and explosion when exposed to extreme heat.

#### **Special Protective Actions**

Wear goggles and use a self-contained breathing apparatus. If water is used, fog nozzles are preferred.

# **SECTION 6) ACCIDENTAL RELEASE MEASURES**

#### **Emergency Procedure**

Avoid breathing vapors. Ventilate area. Remove all sources of ignition.

### **Recommended Equipment**

497720 Page 2 of 7

Clean up with an absorbent material and place in closed containers for disposal.

#### **Personal Precautions**

Wear safety glasses and gloves.

### **Environmental Precautions**

Stop spill/release if it can be done safely.

# **SECTION 7) HANDLING AND STORAGE**

#### General

Do not puncture or incinerate (burn) cans. Do not stick pins, nails, or any other sharp objects into opening on top of can. Do not spray in eyes. Do not take internally.

### **Ventilation Requirements**

Use in a well ventilated place.

#### **Storage Room Requirements**

Store and use in a cool, dry, well-ventilated area. Do not store above 120°F. See product label for additional information.

# **SECTION 8) EXPOSURE CONTROLS, PERSONAL PROTECTION**

#### **Eye Protection**

Safety glasses with side shields should be used if indicated. Eye wash and safety showers in the workplace are recommended.

#### **Skin Protection**

Use solvent-resistant protective gloves for prolonged or repeated contact.

# **Respiratory Protection**

Avoid breathing vapors. In restricted areas, use approved chemical/mechanical filters designed to remove a combination of particles and vapor. In confined areas, use an approved air line respirator or hood. A self-contained breathing apparatus is required for vapor concentrations above PEL/TLV limits.

# **Appropriate Engineering Controls**

Ventilation should be sufficient to prevent inhalation of any vapors.

Chemical Name	OSHA TWA (ppm)	OSHA TWA (mg/m3)	OSHA STEL (ppm)	OSHA STEL (mg/m3)	OSHA Tables (Z1, Z2, Z3)	OSHA Carcinogen	OSHA Skin designation	NIOSH TWA (ppm)	NIOSH TWA (mg/m3)	NIOSH STEL (ppm)	NIOSH STEL (mg/m3)	NIOSH Carcinogen
BUTANE								800	1900			
PROPANE	1000	1800			1			1000	1800			

Chemical Name	ACGIH TWA (ppm)	ACGIH TWA (mg/m3)	ACGIH STEL (ppm)	ACGIH STEL (mg/m3)
BUTANE	1000			
PROPANE	See Appendix F: Minimal Oxygen Content			

(C) - Ceiling limit

497720 Page 3 of 7

# **SECTION 9) PHYSICAL AND CHEMICAL PROPERTIES**

# **Physical and Chemical Properties**

Density	6.52 lb/gal
Density VOC	0.65 lb/gal
% VOC	10%

Appearance N.A.
Odor Threshold N.A.
Odor Description N.A.
pH N.A.
Water Solubility N.A.

Flammability Flash point below 73°F / 23°C

Flash Point Symbol N.A. Flash Point N.A. Viscosity N.A. Lower Explosion Level N.A. Upper Explosion Level N.A. Vapor Density N.A. Melting Point N.A. Freezing Point N.A. Low Boiling Point N.A. High Boiling Point N.A. Decomposition Pt N.A. Auto Ignition Temp N.A.

Evaporation Rate Slower than ether

# **SECTION 10) STABILITY AND REACTIVITY**

# **Stability**

The product is stable under normal storage conditions.

# **Conditions to Avoid**

High temperatures.

#### **Incompatible Materials**

No data available.

### **Hazardous Reactions/Polymerization**

None known.

### **Hazardous Decomposition Products**

Hazardous decomposition products may include carbon dioxide, carbon monoxide, and other toxic fumes.

# **SECTION 11) TOXICOLOGICAL INFORMATION**

#### Skin Corrosion/Irritation

497720 Page 4 of 7

No data available

#### Classification of the substance or mixture

There is no ecological data available for this product.

### Serious Eye Damage/Irritation

No data available

# Carcinogenicity

No data available

### **Germ Cell Mutagenicity**

No data available

### **Reproductive Toxicity**

No data available

### Respiratory/Skin Sensitization

No data available

# **Specific Target Organ Toxicity - Single Exposure**

No data available

# **Specific Target Organ Toxicity - Repeated Exposure**

No data available

#### **Aspiration Hazard**

No data available

### **Acute Toxicity**

0000106-97-8 BUTANE

LC50 (mouse): 202000 ppm (481000 mg/m3) (4-hour exposure); cited as 680 mg/L (2-hour exposure) (9) LC50 (rat): 276000 ppm (658000 mg/m3) (4-hour exposure); cited as 658 mg/L (4- hour exposure) (9)

# **SECTION 12) ECOLOGICAL INFORMATION**

**Toxicity** 

No data available

### Persistence and Degradability

No data available.

#### **Bio-Accumulative Potential**

No data available.

### **Mobility in Soil**

No data available.

### **Other Adverse Effects**

No data available.

# **SECTION 13) DISPOSAL CONSIDERATIONS**

#### **Water Disposal**

Under RCRA, it is the responsibility of the user of the product, to determine at the time of disposal whether the product meets RCRA criteria for hazardous waste. Waste management should be in full compliance with federal, state, and local laws.

Empty containers retain product residue which may exhibit hazards of material, therefore do not pressurize, cut, glaze, weld or use for any other purposes. Return drums to reclamation centers for proper cleaning and reuse.

# **SECTION 14) TRANSPORT INFORMATION**

# **U.S. DOT Information**

UN number: UN1950

Proper shipping name: Aerosols, flammable, (each not exceeding 1 L capacity) (LTD QTY)

Hazard class: 2.1

### **IMDG Information**

UN number: UN1950

Proper shipping name: Aerosols, flammable, (each not exceeding 1 L capacity) (LTD QTY)

Hazard class: 2.1

### **IATA Information**

UN number: UN1950 Hazard class: 2.1

Proper shipping name: Aerosols, flammable, (each not exceeding 1 L capacity) (N/A)

# **SECTION 15) REGULATORY INFORMATION**

CAS	Chemical Name	% By Weight	Regulation List
0008042-47-5	MINERAL OIL, SLAB OIL	51% - 90%	SARA312,TSCA
0000074-98-6	PROPANE	5% - 11%	SARA312,VOC,TSCA,ACGIH,OSHA
0067784-80-9	Soybean oil, Me ester	5% - 10%	SARA312,TSCA
0000106-97-8	BUTANE	2% - 4%	SARA312,VOC,TSCA,ACGIH


# **SECTION 16) OTHER INFORMATION**

497720 Page 6 of 7

#### **Glossary**

\* There are points of differences between OSHA GHS and UN GHS. In 90% of the categories, they can be used interchangeably, but for the Skin Corrosion/Irritant Category and the Specific Target Organ Toxicity (Single and Repeated Exposure) Categories. In these cases, our system will say UN GHS.

ACGIH- American Conference of Governmental Industrial Hygienists; ANSI- American National Standards Institute; Canadian TDG-Canadian Transportation of Dangerous Goods; CAS- Chemical Abstract Service; Chemtrec- Chemical Transportation Emergency Center (US); CHIP- Chemical Hazard Information and Packaging; DSL- Domestic Substances List; EC- Equivalent Concentration; EH40 (UK)-HSE Guidance Note EH40 Occupational Exposure Limits; EPCRA- Emergency Planning and Community Right-To-Know Act; ESL-Effects screening levels; HMIS- Hazardous Material Information Service; LC- Lethal Concentration; LD- Lethal Dose; NFPA- National Fire Protection Association; OEL- Occupational Exposure Limits; OSHA- Occupational Safety and Health Administration, US Department of Labor; PEL- Permissible Exposure Limit; SARA (Title III)- Superfund Amendments and Reauthorization Act; SARA 313- Superfund Amendments and Reauthorization Act, Section 313; SCBA- Self-Contained Breathing Apparatus; STEL- Short Term Exposure Limit; TCEQ- Texas Commission on Environmental Quality; TLV- Threshold Limit Value; TSCA- Toxic Substances Control Act Public Law 94-469; TWA- Time Weighted Value; US DOT- US Department of Transportation; WHMIS- Workplace Hazardous Materials Information System.



(\*) - Chronic effects

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks

#### **DISCLAIMER**

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist. The above information pertains to this product as currently formulated, and is based on the information available at this time. Addition of reducers or other additives to this product may substantially alter the composition and hazards of the product. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.

497720 Page 7 of 7