



HIVETM

HIVE 500 PLUS

Receiver



FEATURES

- 500 transmitter memory
- Block programming
- Pulse, step or timed mode
- 1 second to 24 hour delay
- 12-24 VAC/DC
- 433 MHz

Preferred Accessories:

- Master Programmer Transmitter (Must be 2 or more buttons)
- Memory Stick

SPECIFICATIONS

Receiver type:	Supereheterodyne
Demodulation:	AM/ASK
Sensitivity (for good signal):	-115 dBm.
Input load:	50 Ohm
Current consumption	(@12Vdc) from 25 mA to 90 mA (max)
N° of relays:	2 (1 NO and 1NO / NC)
Max power on relay output:	24VA max 60V
Security protocol:	Keeloq Hopping code
N° of code combinations	2exp64
Operating temperature:	-20 to + 70 °C.
Dimensions:	120 x 80 x 40 mm
Weight:	65 gr



PIERCE BUILDING: 3788 WEST 2270 SOUTH, SUITE E
SALT LAKE CITY, UT 84120
(866) 975-0101 • (866) 975-0404 FAX
WWW.TRANSMITTERSOLUTIONS.COM

All items are trademarks of their respective holders.

To have your fax number removed from future specials, please call Removal Services - 800-915-2571 ext. 47540 or fax to 866-975-0404.