

PUSHING FOR BETTER SOLUTIONS

**PassAbility™**



# Double Standard Electromagnetic Lock

## FEATURES:

### SPECIFICATIONS:

**Operating Voltage:** 12/24VDC (auto-switchable)

**Current Draw:** 500mA/12VDC; 250mA/24VDC  
(at temperature 20°C)

**Operating Temperature:** -10~55°C (14~131°F)

**Humidity:** 0~95% non-condensing.

**Holding Force:** up to 1200 lbs x 2 (545 Kg x 2)

#### Dimensions:

Magnet: (L) 534, (W) 40, (D) 68mm

Armature plate: (L) 185, (W) 61, (D) 16mm x2

Mounting plate: (L) 534, (W) 40, (D) 5mm

**Net Weight:** 9.8Kg

Surface finish for magnet and armature plate: Zinc plated

Epoxy potting compound rating: E87252 (S) UL94V-0

### FUNCTIONS & FEATURES:

- Low maintenance with high reliability
- Easy installation
- New style mounting plate with increased immobility
- Aluminum anodized casing
- MOV prevents spike and surge current
- Dual voltage 12/24 VDC (auto-switchable)
- Anti-residual magnetism function (ARM)



7380 S. Eastern Avenue, Suite 124-320 • Las Vegas, NV 89123

All items are trademarks of their respective holders.

To have your fax number removed from future specials, please call Removal Services - 800-915-2571 ext. 47540 or fax to 866-975-0404.