

PUSHING FOR BETTER SOLUTIONS

**PassAbility™**



# Standard Weatherproof Electromagnetic Lock



## FEATURES:

### SPECIFICATIONS:

#### Operating Voltage:

Single Voltage: 12 or 24VDC  
Dual Voltage: 12/24VDC

#### Current Draw:

Single Voltage: 460mA/12VDC, 250mA/24VDC  
Dual Voltage: 500mA/12VDC, 250mA/24VDC  
(at temperature 20°C)

**Operating Temperature:** -10~55°C (14~131°F)

**Humidity:** 0~95% non-condensing.

**Holding Force:** 1200 lbs (545 Kg)

**Bond sensor output:** 0.5A/20VDC

#### Dimensions:

Magnet: (L) 220, (W) 68, (D) 41 mm  
Armature Plate: (L) 185, (W) 62, (D) 16 mm

**Net Weight:** 5.0Kg

Surface finish for magnet and armature plate: Zinc plated

Epoxy potting compound rating: E87252 (S) UL94V-0

### FUNCTIONS & FEATURES:

- Low maintenance with high reliability
- Stainless steel casing
- High reliability
- Dual voltage 12 or 24 VDC (selectable)
- MOV provides spike and surge protection
- Anti-Residual magnetism function
- Holding force up to 1200lbs

7380 S. Eastern Avenue, Suite 124-320 • Las Vegas, NV 89123

All items are trademarks of their respective holders.

To have your fax number removed from future specials, please call Removal Services - 800-915-2571 ext. 47540 or fax to 866-975-0404.