

LOOP SIZES & CHARACTERISTICS

Loop Size Length	Loop Size Width	Inductance	Turns	Detection Height Feet
2 (0.61m)	2 (0.61m)	60	5	1.6 (0.488m)
2 (0.61m)	4 (1.22m)	60	4	1.6 (0.488m)
2 (0.61m)	6 (1.83m)	80	4	1.6 (0.488m)
2 (0.61m)	8 (2.44m)	60	3	1.6 (0.488m)
2 (0.61m)	10 (3.05m)	72	3	1.6 (0.488m)
2 (0.61m)	12 (3.66m)	84	3	1.6 (0.488m)
2 (0.61m)	14 (4.27m)	96	3	1.6 (0.488m)
2 (0.61m)	16 (4.88m)	108	3	1.6 (0.488m)
2 (0.61m)	18 (5.49m)	120	3	1.6 (0.488m)
2 (0.61m)	20 (6.10m)	132	3	1.6 (0.488m)

4 (1.22m)	4 (1.22m)	80	4	3.2 (0.975m)
4 (1.22m)	6 (1.83m)	100	4	3.2 (0.975m)
4 (1.22m)	8 (2.44m)	72	3	3.2 (0.975m)
4 (1.22m)	10 (3.05m)	84	3	3.2 (0.975m)
4 (1.22m)	12 (3.66m)	96	3	3.2 (0.975m)
4 (1.22m)	14 (4.27m)	108	3	3.2 (0.975m)
4 (1.22m)	16 (4.88m)	120	3	3.2 (0.975m)
4 (1.22m)	18 (5.49m)	132	3	3.2 (0.975m)
4 (1.22m)	20 (6.10m)	144	3	3.2 (0.975m)
4 (1.22m)	22 (6.71m)	156	3	3.2 (0.975m)
4 (1.22m)	24 (7.32m)	168	3	3.2 (0.975m)
4 (1.22m)	26 (7.93m)	180	3	3.2 (0.975m)
4 (1.22m)	28 (8.54m)	192	3	3.2 (0.975m)
4 (1.22m)	30 (9.14m)	102	2	3.2 (0.975m)
4 (1.22m)	32 (9.75m)	108	2	3.2 (0.975m)
4 (1.22m)	33 (10.06m)	111	2	3.2 (0.975m)
4 (1.22m)	34 (10.36m)	114	2	3.2 (0.975m)
4 (1.22m)	36 (10.97m)	120	2	3.2 (0.975m)
4 (1.22m)	38 (11.58m)	126	2	3.2 (0.975m)
4 (1.22m)	40 (12.20m)	132	2	3.2 (0.975m)



EMX Industries, Inc.

4564 Johnston Parkway, Cleveland, Ohio 44128

P. 800 426 9912 F. 216 518 9884

Sales Inquiries: salesupport@emxinc.com **Technical Support:** technical@emxinc.com

www.emxinc.com

Loop Size Length	Loop Size Width	Inductance	Turns	Detection Height Feet
6 (1.83m)	6 (1.83m)	120	4	4.8 (1.463m)
6 (1.83m)	8 (2.44m)	84	3	4.8 (1.463m)
6 (1.83m)	10 (3.05m)	96	3	4.8 (1.463m)
6 (1.83m)	12 (3.66m)	108	3	4.8 (1.463m)
6 (1.83m)	14 (4.27m)	120	3	4.8 (1.463m)
6 (1.83m)	16 (4.88m)	132	3	4.8 (1.463m)
6 (1.83m)	18 (5.49m)	144	3	4.8 (1.463m)
6 (1.83m)	20 (6.10m)	178	2	4.8 (1.463m)
6 (1.83m)	22 (6.71m)	84	2	4.8 (1.463m)
6 (1.83m)	24 (7.32m)	90	2	4.8 (1.463m)
6 (1.83m)	26 (7.93m)	96	2	4.8 (1.463m)
6 (1.83m)	28 (8.54m)	102	2	4.8 (1.463m)
6 (1.83m)	30 (9.14m)	108	2	4.8 (1.463m)
6 (1.83m)	32 (9.75m)	114	2	4.8 (1.463m)
6 (1.83m)	33 (10.06m)	117	2	4.8 (1.463m)
6 (1.83m)	34 (10.36m)	120	2	4.8 (1.463m)
6 (1.83m)	36 (10.97m)	126	2	4.8 (1.463m)
6 (1.83m)	38 (11.58m)	132	2	4.8 (1.463m)
6 (1.83m)	40 (12.20m)	138	2	4.8 (1.463m)

8 (2.44m)	4 (1.22m)	120	4	3.2 (0.975m)
8 (2.44m)	6 (1.83m)	140	4	4.8 (1.463m)
8 (2.44m)	8 (2.44m)	96	3	5.6 (1.71m)
8 (2.44m)	10 (3.05m)	108	3	5.6 (1.71m)
8 (2.44m)	12 (3.66m)	120	3	5.6 (1.71m)
8 (2.44m)	14 (4.27m)	132	3	5.6 (1.71m)
8 (2.44m)	16 (4.88m)	144	3	5.6 (1.71m)
8 (2.44m)	18 (5.49m)	78	2	5.6 (1.71m)
8 (2.44m)	20 (6.10m)	84	2	5.6 (1.71m)
8 (2.44m)	22 (6.71m)	90	2	5.6 (1.71m)
8 (2.44m)	24 (7.32m)	96	2	5.6 (1.71m)
8 (2.44m)	26 (7.93m)	102	2	5.6 (1.71m)
8 (2.44m)	28 (8.54m)	108	2	5.6 (1.71m)
8 (2.44m)	30 (9.14m)	114	2	5.6 (1.71m)
8 (2.44m)	32 (9.75m)	120	2	5.6 (1.71m)
8 (2.44m)	33 (10.06m)	123	2	5.6 (1.71m)
8 (2.44m)	34 (10.36m)	126	2	5.6 (1.71m)
8 (2.44m)	36 (10.97m)	132	2	5.6 (1.71m)
8 (2.44m)	38 (11.58m)	138	2	5.6 (1.71m)
8 (2.44m)	40 (12.20m)	144	2	5.6 (1.71m)

All the figures are approximate, actual results may vary

Serial resistance: Between leads is to be less than 5 Ohms

Leakage to ground: Between one lead wire and the ground should be more than 10 mega ohm at 500 VDC for one minute. Use DI 6200 insulation tester or equivalent. (older loops may be to 1 mega ohm)

Lead wires should be twisted at least 6 turns per foot (0.305m)