

DAK-USVD

DRIVE-THRU ALERT KIT

The drive-thru alert kit is comprised of two components: the CHIME-100 sound module, which provides an audio indication to team members and the USVD-4X ultrasonic vehicle detector, which detects the presence of a vehicle. This system can be used in a wide variety of drive-thru applications, including parking, access control, car wash, banking and fast food.

The CHIME-100 provides an audible chime when a vehicle first pulls in front of the vehicle detector. It is a compact, audio alert device designed for loud work environments. The CHIME-100 has an adjustable volume control and can reach volumes of 100 dBA at 5 ft away making it easy to hear in noisy areas. It is easy to install with two mounting tabs and includes 25 ft of durable cable for connection to the USVD-4X. The CHIME-100 also features an output relay for daisy-chaining additional electronics and 6 melodies to choose from.

The USVD-4X is mounted on a post, order box, or the side of a building and aimed at the desired location for vehicle detection. No additional set-up or functional adjustments are necessary – unlike other vehicle detection systems. Also unlike other technologies, the USVD-4X does not require the installation of an inductive loop in the pavement. The detection head consists of 4 ultrasonic transducers that connect to the internal microprocessor-based control board. The USVD-4X "scans" the expected location for a vehicle and activates its output upon detection of a vehicle. It operates on 2-24 VDC/AC and provides two Form C relay contacts for vehicle presence detection, as well as Pulse on Entry, Pulse on Exit, or both.



Drive-Thru Alert Kit

- · Audible chime in loud work environments
- Easy set-up for streamline operation
- · Ultrasonic vehicle detection technology
- Auxiliary relay settings Pulse on Entry, Pulse on Exit, or both
- Output delay option for 1, 2 or 4 seconds









USVD-4X

CHIME-100 Technical Data

Supply Voltage 9 VDC

Dimensions 4.5" (114 mm) x 3.25" (83 mm) x 1.58" (40 mm)

Weight 0.35 lbs
Housing Polycarbonate
Maximum Volume 100 dBA @ 5 ft

Melody Options

Included Cable 25 ft – 5 conductors (0.25" outer diameter)

USVD-4X Technical Data

Sensing Elements | 4 ultrasonic transducers

Operating Range
Response Time
Relay Output Configuration
Relay Contact Rating

1-5 ft
2.0 seconds
2 SPDT (Form C)
1 A @ 24 VDC

Power Indicator/No Vehicle
Object In Range
Green LED
Flashing green LED on each input, continuous LED on detect

Supply Voltage 12-24 VDC/AC

Operating Current
Operating Temperature

60 mA
-40°C to 85°C (-40°F to 182°F)

Dimensions 5.7"(145 mm) x 3.6"(90 mm) x 2.3"(57 mm)

Weight 0.6 lbs (275 g)
Housing ABS NEMA 4X

Connection 10 position terminal block

Ordering Information

 DAK-USVD Drive-Thru Alert Kit, includes USVD-4X ultrasonic vehicle detector and CHIME-100 sound module with volume control













